

HIGH PERFORMANCE POLYCRYSTALLINE MODULE

RSM60-6-270P-290P

60 CELL POLYCRYSTALLINE MODULE

270-290Wp POWER OUTPUT RANGE

1500VDC MAXIMUM SYSTEM VOLTAGE

17.7% MAXIMUM EFFICIENCY



About Risen Energy

Risen Energy is a leading, global tier 1 manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation. The company, founded in 1986, and publicly listed in 2010, compels value generation for its chosen global customers. Techno-commercial innovation, underpinned by consummate quality and support, encircle Risen Energy's total Solar PV business solutions which are among the most powerful and cost-effective in the industry. With local market presence and strong financial bankability status, we are committed, and able, to building strategic, mutually beneficial collaborations with our partners, as together we capitalise on the rising value of green energy.

KEY SALIENT FEATURES



Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing



Industry leading lowest thermal co-efficient of power



Industry leading 12 years product warranty



Excellent low irradiance performance



Excellent PID resistance



Positive tight power tolerance



Dual stage 100% EL Inspection warranting defect-free product



Module Imp binning radically reduces string mismatch losses



Warranted reliability and stringent quality assurances well beyond certified requirements



Certified to withstand severe environmental conditions

- Anti-reflective & anti-soiling surface minimise power loss from dirt and dust
- Severe salt mist, ammonia & blown sand resistance, for seaside, farm and desert environments
- Excellent mechanical load 2400Pa & snow load 5400Pa resistance




ISO9001
ISO14001
OHSAS18001
IEC TS 62941






LINEAR PERFORMANCE WARRANTY

12 year Product Warranty / 25 year Linear Power Warranty



THE POWER OF RISING VALUE

Dimensions of PV Module



Our Partners:

ELECTRICAL DATA (STC)

Model Number	RSM60-6-270P	RSM60-6-275P	RSM60-6-280P	RSM60-6-285P	RSM60-6-290P
Rated Power in Watts-Pmax(Wp)	270	275	280	285	290
Open Circuit Voltage-Voc(V)	37.90	38.10	38.30	38.40	38.60
Short Circuit Current-Isc(A)	9.20	9.30	9.40	9.50	9.60
Maximum Power Voltage-Vmpp(V)	31.05	31.25	31.50	31.70	31.90
Maximum Power Current-Imp(A)	8.70	8.80	8.90	9.00	9.10
Module Efficiency (%)	16.5	16.8	17.1	17.4	17.7

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

ELECTRICAL DATA (NMOT)

Model Number	RSM60-6-270P	RSM60-6-275P	RSM60-6-280P	RSM60-6-285P	RSM60-6-290P
Maximum Power-Pmax (Wp)	201.4	205.1	209.1	212.8	216.5
Open Circuit Voltage-Voc (V)	34.90	35.00	35.20	35.30	35.50
Short Circuit Current-Isc (A)	7.54	7.63	7.71	7.79	7.87
Maximum Power Voltage-Vmpp (V)	28.40	28.60	28.80	29.00	29.20
Maximum Power Current-Imp (A)	7.09	7.17	7.25	7.34	7.42

NMOT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	Polycrystalline, 5BB
Cell configuration	60 cells (6×10)
Module dimensions	1650×992×35mm
Weight	18kg
Superstrate	3.2 mm, High Transmission, Low Iron, Tempered ARC Glass
Substrate	White Back-sheet
Frame	Anodized Aluminium Alloy type 6063T5, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm ² (12AWG), 900mm length
Connector	Risen Twinsel PV-SY02, IP68

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	45°C±2°C
Temperature Coefficient of Voc	-0.32%/°C
Temperature Coefficient of Isc	0.055%/°C
Temperature Coefficient of Pmax	-0.39%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	20A
Limiting Reverse Current	20A

PACKAGING CONFIGURATION

	40ft	20ft
Number of modules per container	840	360
Number of modules per pallet	30	30
Number of pallets per container	28	12
Packaging box dimensions (LxWxH) in mm	1680×1105×1130	1680×1105×1130
Box gross weight[kg]	590	590

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
©2019 Risen Energy. All rights reserved. Specifications included in this datasheet are subject to change without notice.

THE POWER OF RISING VALUE